

34000A 系列

超高功率直流電子負載



HIGH POWER DC ELECTRONIC LOAD



博計電子股份有限公司

新北市新店區寶中路88號8樓

TEL : 886-2-2918-2620

FAX : 886-2-2912-9870

[http : //www.prodigit.com.tw](http://www.prodigit.com.tw) E-mail : carry@prodigit.com.tw





特 性

- 最大功率可達 320KW
- 最高達 8 台主/從並聯控制
- 5位數之數位電壓、電流以及功率錶
- 高速量測及通訊傳輸速率
- 大型 LCD Display、可用飛梭旋鈕或按鍵調整設定值
- 可同時顯示電壓值、電流值、瓦特值
- 適用於功率因數調整器(PFC)測試用 (600V,1000V機種)
- 可自動執行OCP、OPP測試
- 可設定開機狀態值
- 定電流、定電阻、定電壓、定功率、定電流+定電壓、定功率+定電壓、動態及短路模式
- 於短路測試時可設定短路時間
- 過電流、功率、溫度保護及過電壓示警
- 電壓極性顯示可設成正值(“+”)或負值(“-”)
- 支援太陽能板MPPT CC、CR、CV測試
- 可選用介面： GPIB、RS232、USB、LAN

說 明

- 34000A系列具有獨立的控制及顯示面板、定電流/定電阻/定電壓/定功率/動態模式，配合面板上的150組 儲存/呼叫 記憶，能有效地控制所有負載的設定，更可透過RS232、Ethernet、USB和GPIB等介面進行遠端控制。
- 具備短路測試功能及設定短路時間，並可量測短路電壓及電流。
- 在定電流及定功率模式下，可做動態負載之模擬，其電流上升、下降斜率均為獨立可調，另具有-外部輸入任意波形之動態負載功能。
- 具有OCP、OPP單鍵測試功能，使得OCP、OPP之測試更有效率及準確。
- 可設定的吃載/停止吃載(LOAD ON/OFF)電壓點及良/不良(GO/NG)的比較判斷功能、電壓極性顯示可正可負及150組 儲存/呼叫 記憶，使得負載更適用於各種不同的應用。
- 多達150組測試參數及狀態的儲存功能，讓其可根據自動測試 (auto sequence) 需求，隨時將儲存記憶調出來任意使用。
- 因其耐壓可高達1000V，故而非常適用於功率因數調整器 (PFC) 的測試應用。
- 主/從控制最多為1個MASTER，7個SLAVE

應 用

- 電壓/電流源測試
- 交換式電源供應器暫態響應
- 定電壓模式供限流測試及模擬電池
- 電池放電
- 電池充電
- 研發、品管
- ATE系統
- 生產測試

規 格

MODEL	34105A		34110A		34115A		34120A		34125A	
Power	5KW		10KW		15KW		20KW		25KW	
Current	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A
Voltage	0 ~ 60V		0 ~ 60V		0 ~ 60V		0 ~ 60V		0 ~ 60V	
Min. Operating Voltage	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³
Protections										
Over Power Protection (OPP)					105%					
Over Current Protection (OCP)					104%					
Over Voltage Protection (OVP)					105%					
Over Temp Protection (OTP)					Yes					
Constant Current Mode										
Range ¹	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA
Accuracy	± (0.1% of Setting + 0.2% of Range)									
Constant Resistance Mode										
Range	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω
Resolution	277μS	0.001mΩ	277μS	0.001mΩ	277μS	0.001mΩ	277μS	0.001mΩ	277μS	0.001mΩ
Accuracy	± 0.2% of (Setting + Range)									
Constant Voltage Mode										
Range	60V									
Resolution	1mV									
Accuracy	± 0.05% of (Setting + Range)									
Constant Power Mode										
Range	500W	5000W	1000W	10000W	1500W	15000W	2000W	20000W	2500W	25000W
Resolution	8mW	80mW	16mW	160mW	24mW	240mW	32mW	320mW	40mW	400mW
Accuracy	± 0.5% of (Setting + Range)									
Constant Voltage Mode + Constant Current Mode										
Range	60V	1000A	60V	1000A	60V	1000A	60V	1000A	60V	1000A
Resolution	1mV	16mA	1mV	16mA	1mV	16mA	1mV	16mA	1mV	16mA
Accuracy	± 1.0% of (Setting + Range)									
Constant Voltage Mode + Constant Power Mode										
Range	60V	5000W	60V	10000W	60V	15000W	60V	20000W	60V	25000W
Resolution	1mV	80mW	1mV	160mW	1mV	240mW	1mV	320mW	1mV	400mW
Accuracy	± 1.0% of (Setting + Range)									
MPPT Mode										
Algorithm	P&O + Scanning									
Load mode	CC, CR, CV (MPPT C, R, V)									
Sampling interval	10ms~2000ms ; resolution 1ms									
P&O interval	10ms~2000ms ; resolution 1ms									
Memory situation	Discard old data and keep catching new data									
Dynamic Mode										
Timing										
Thigh & Tlow	0.150~9.999 / 99.99 / 999.9 / 9999ms									
Resolution	0.001 / 0.01 / 0.1 / 1ms									
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm									
Slew Rate	24mA~1.5A/μs	240mA~15A/μs	24mA~1.5A/μs	240mA~15A/μs	24mA~1.5A/μs	240mA~15A/μs	24mA~1.5A/μs	240mA~15A/μs	24mA~1.5A/μs	240mA~15A/μs
Resolution	6mA/μs	60mA/μs	6mA/μs	60mA/μs	6mA/μs	60mA/μs	6mA/μs	60mA/μs	6mA/μs	60mA/μs
Min. Rise Time	66.7μs(typical)									
Current										
Range	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA
Measurement										
Voltage Read Back										
Range (5 Digital)	0~6V	6~60V	0~6V	6~60V	0~6V	6~60V	0~6V	6~60V	0~6V	6~60V
Resolution	0.1mV	1mV	0.1mV	1mV	0.1mV	1mV	0.1mV	1mV	0.1mV	1mV
Accuracy	± 0.025% of (Reading + Range)									
Current Read Back										
Range (5 Digital)	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA
Accuracy	± 0.1% of (Reading + Range)									
Power Read Back										
Range (5 Digital)	1000W	5000W	1000W	10000W	10000W	15000W	10000W	20000W	10000W	25000W
Resolution	0.01W	0.1W	0.01W	1W	0.1W	1W	0.1W	1W	0.1W	1W
Accuracy	± 0.125% of (Reading + Range)									
General										
Short Circuit										
Current	1000A									
Load ON Voltage	0.1~25V									
Load OFF Voltage	0~25V									
Power Consumption	600Wmax		1000Wmax		1450Wmax		1900Wmax		2350Wmax	
Operating Temperature ²	0~40°C									
Dimension (HxWxD)	573x647x766mm		573x647x766mm		728x647x766mm		885x647x766mm		1041x647x766mm	
HxWxD (Not included wheels)	469x647x766mm		469x647x766mm		625x647x766mm		781x647x766mm		937x647x766mm	
Weight	100 Kg		130 kg		170 kg		220 kg		280 kg	
Safety & EMC	CE									

冷卻方式：智慧型風扇冷卻

輸入電源：① Load-20KW內(含)：100~230 Vac ±10%，50/60Hz

② Load-25KW以上(含)：200~230 Vac ±10%，50/60Hz

註*1:CC Mode 可強制於range II

註*2:操作溫度範圍為0~40°C，此規格表內之精確度僅適用於25°C±5°C

訂 購 方 式

選購介面：

- ① GPIB Card
- ② RS232 Card
- ③ USB Card
- ④ LAN Card

選購配件：

吊環



34105A 60V,1000A,5KW

34110A 60V,1000A,10KW

34115A 60V,1000A,15KW

34120A 60V,1000A,20KW

34125A 60V, 1000A, 25KW

規 格

MODEL	34130A		34135A		34140A		34205A		34210A	
Power	30KW		35KW		40KW		5KW		10KW	
Current	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0 ~ 16A	0 ~ 160A	0 ~ 32A	0 ~ 320A
Voltage	0 ~ 60V									
Min. Operating Voltage	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³	10V@160A		10V@320A	
Protections										
Over Power Protection (OPP)	105%						105%			
Over Current Protection (OCP)	104%						105%			
Over Voltage Protection (OVP)	105%						105%			
Over Temp Protection (OTP)	Yes									
Constant Current Mode										
Range ¹	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0 ~ 16A	0 ~ 160A	32A	320A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	0.256mA	2.56mA	0.512mA	5.12mA
Accuracy	± (0.1% of Setting + 0.2% of Range)									
Constant Resistance Mode										
Range	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω	15000Ω~3.75Ω	3.75Ω~0.063Ω	12500Ω~1.875Ω	1.875Ω~0.0315Ω
Resolution	277μS	0.001mΩ	277μS	0.001mΩ	277μS	0.001mΩ	4.4μS	63μΩ	8.8μΩ	0.0315mΩ
Accuracy	± 0.2% of (Setting + Range)									
Constant Voltage Mode										
Range	60V						600V			
Resolution	1mV						10mV			
Accuracy	± 0.05% of (Setting + Range)									
Constant Power Mode										
Range	3000W	30000W	3500W	35000W	4000W	40000W	500W	5000W	1000W	10000W
Resolution	48mW	480mW	56mW	560mW	64mW	640mW	8mW	80mW	16mW	160mW
Accuracy	± 0.5% of (Setting + Range)									
Constant Voltage Mode + Constant Current Mode										
Range	60V	1000A	60V	1000A	60V	1000A	600V	160A	600V	320A
Resolution	1mV	16mA	1mV	16mA	1mV	16mA	10mV	2.56mA	10mV	5.12mA
Accuracy	± 1.0% of (Setting + Range)									
Constant Voltage Mode + Constant Power Mode										
Range	60V	30000W	60V	35000W	60V	40000W	600V	5000W	600V	10000W
Resolution	1mV	480mW	1mV	560mW	1mV	640mW	10mV	80mW	10mV	160mW
Accuracy	± 1.0% of (Setting + Range)									
MPPT Mode										
Algorithm	P&O + Scanning									
Load mode	CC, CR, CV (MPPT C, R, V)									
Sampling interval	10ms~2000ms ; resolution 1ms									
P&O interval	10ms~2000ms ; resolution 1ms									
Memory situation	Discard old data and keep catching new data									
Dynamic Mode										
Timing										
Thigh & Tlow	0.150~9.999 / 99.99 / 999.9 / 9999ms									
Resolution	0.001 / 0.01 / 0.1 / 1ms									
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm									
Slew Rate	24mA~1.5A/uS	240mA~15A/uS	24mA~1.5A/uS	240mA~15A/uS	24mA~1.5A/uS	240mA~15A/uS	12.8mA~800mA/uS	128mA~8A/uS	25.6mA~1.6A/uS	256mA~16A/uS
Resolution	6mA/uS	60mA/uS	6mA/uS	60mA/uS	6mA/uS	60mA/uS	3.2mA/uS	32mA/uS	6.4mA/uS	64mA/uS
Min. Rise Time	66.7μs(typical)						20μs(typical)			
Current										
Range	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~16A	16~160A	0~32A	32~320A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	0.256mA	2.56mA	0.512mA	5.12mA
Measurement										
Voltage Read Back										
Range (5 Digital)	0~6V	6~60V	0~6V	6~60V	0~6V	6~60V	0~60V	60~600V	0~60V	60~600V
Resolution	0.1mV	1mV	0.1mV	1mV	0.1mV	1mV	1mV	10mV	1mV	10mV
Accuracy	± 0.025% of (Reading + Range)									
Current Read Back										
Range (5 Digital)	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~16A	16~160A	0~32A	32~320A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	0.256mA	2.56mA	0.512mA	5.12mA
Accuracy	± 0.1% of (Reading + Range)									
Power Read Back										
Range (5 Digital)	10000W	30000W	10000W	35000W	10000W	40000W	1000W	5000W	1000W	10000W
Resolution	0.1W	1W	0.1W	1W	0.1W	1W	0.01W	0.1W	0.01W	1W
Accuracy	± 0.125% of (Reading + Range)									
General										
Short Circuit										
Current	1000A						160A		320A	
Load ON Voltage	0.1~25V						0.4 ~ 100V		0.4 ~ 100V	
Load OFF Voltage	0~25V									
Power Consumption	2800Wmax		3250Wmax		3700Wmax		600Wmax		1000Wmax	
Operating Temperature ²	0~40°C									
Dimension (HxWxD)	1197x647x766mm		1353x647x766mm		1509x647x766mm		573x647x766mm		573x647x766mm	
HxWxD (Not included wheels)	1093x647x766mm		1249x647x766mm		1405x647x766mm		469x647x766mm		469x647x766mm	
Weight	340 Kg		390 kg		430 kg		100 kg		130 kg	
Safety & EMC										
CE										

冷卻方式：智慧型風扇冷卻

輸入電源：① Load-20KW內(含)：100~230 Vac ±10%，50/60Hz

② Load-25KW以上(含)：200~230 Vac ±10%，50/60Hz

註*1:CC Mode 可強制於range II

註*2:操作溫度範圍為0~40°C，此規格表內之精確度僅適用於25°C±5°C

訂 購 方 式

選購介面：

- ① GPIB Card
- ② RS232 Card
- ③ USB Card
- ④ LAN Card

選購配件：

吊環



34130A 60V,1000A,30KW

34135A 60V,1000A,35KW

34140A 60V,1000A,40KW

34205A 600V,160A,5KW

34210A 600V,320A,10KW

規 格

MODEL	34215A		34220A		34225A		34230A		34235A		
Power	15KW		20KW		25KW		30KW		35KW		
Current	0 ~ 48A 0 ~ 480A		0 ~ 64A 0 ~ 640A		0 ~ 80A 0 ~ 800A		0 ~ 96A 0 ~ 960A		0 ~ 112A 0 ~ 1120A		
Voltage	0 ~ 600V										
Min. Operating Voltage	10V @ 480A		10V @ 640A		10V @ 800A		10V @ 960A		10V @ 1120A		
Protections											
Over Power Protection (OPP)	105%										
Over Current Protection (OCP)	105%										
Over Voltage Protection (OVP)	105%										
Over Temp Protection (OTP)	Yes										
Constant Current Mode											
Range*1	48A	480A	64A	640A	80A	800A	96A	960A	112A	1120A	
Resolution	0.768mA	7.68mA	1.024mA	10.24mA	1.28mA	12.8mA	1.536mA	15.36mA	1.792mA	17.92mA	
Accuracy	± (0.1% of Setting + 0.2% of Range)										
Constant Resistance Mode											
Range	15000Ω~1.25Ω	1.25Ω~0.021Ω	11250Ω~0.9375Ω	0.9375Ω~0.01575Ω	11250Ω~0.75Ω	0.75Ω~0.0126Ω	12500Ω~0.625Ω	0.625Ω~0.0105Ω	6428.4Ω~0.5357Ω	0.5357Ω~0.009Ω	
Resolution	13.3μs	0.021mΩ	17.7μs	0.01575mΩ	22.2μs	0.0126mΩ	26.6μs	0.0105mΩ	31.1μs	0.009mΩ	
Accuracy	±0.2% of (Setting + Range)										
Constant Voltage Mode											
Range	600V										
Resolution	10mV										
Accuracy	± 0.05% of (Setting + Range)										
Constant Power Mode											
Range	1500W	15000W	2000W	20000W	2500W	25000W	3000W	30000W	3500W	35000W	
Resolution	24mW	240mW	32mW	320mW	40mW	400mW	48mW	480mW	56mW	560mW	
Accuracy	± 0.5% of (Setting + Range)										
Constant Voltage Mode + Constant Current Mode											
Range	600V	480A	600V	640A	600V	800A	600V	960A	600V	1120A	
Resolution	10mV	7.68mA	10mV	10.24mA	10mV	12.8mA	10mV	15.36mA	10mV	17.92mA	
Accuracy	± 1.0% of (Setting + Range)										
Constant Voltage Mode + Constant Power Mode											
Range	600V	15000W	600V	20000W	600V	25000W	600V	30000W	600V	35000W	
Resolution	10mV	240mW	10mV	320mW	10mV	400mW	10mV	480mW	10mV	560mW	
Accuracy	± 1.0% of (Setting + Range)										
MPPT Mode											
Algorithm	P&O + Scanning										
Load mode	CC, CR, CV (MPPT C, R, V)										
Sampling interval	10ms~2000ms ; resolution 1ms										
P&O interval	10ms~2000ms ; resolution 1ms										
Memory situation	Discard old data and keep catching new data										
Dynamic Mode											
Timing											
Thigh & Tlow	0.050~9.999 / 99.99 / 999.9 / 9999ms										
Resolution	0.001 / 0.01 / 0.1 / 1ms										
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm										
Slew Rate	38.4mA~2.4A/μs	384mA~24A/μs	51.2mA~3.2A/μs	512mA~32A/μs	64mA~4A/μs	640mA~40A/μs	76.8mA~4.8A/μs	768mA~48A/μs	0.0896A~5.6A/μs	0.896A~56A/μs	
Resolution	9.6mA/μs	96mA/μs	12.8mA/μs	128mA/μs	16mA/μs	160mA/μs	19.2mA/μs	192mA/μs	22.4mA/μs	224mA/μs	
Min. Rise Time	20μs(typical)										
Current											
Range	0~48A	48~480A	0~64A	64~640A	0~80A	80~800A	0~96A	96~960A	0~112A	112~1120A	
Resolution	0.768mA	7.68mA	1.024mA	10.24mA	1.28mA	12.8mA	1.536mA	15.36mA	1.792mA	17.92mA	
Measurement											
Voltage Read Back											
Range (5 Digital)	0~60V	60~600V	0~60V	60~600V	0~60V	60~600V	0~60V	60~600V	0~60V	60~600V	
Resolution	1mV	10mV	1mV	10mV	1mV	10mV	1mV	10mV	1mV	10mV	
Accuracy	±0.025% of (Reading + Range)										
Current Read Back											
Range (5 Digital)	0~48A	48~480A	0~64A	64~640A	0~80A	80~800A	0~96A	96~960A	0~112A	112~1120A	
Resolution	0.768mA	7.68mA	1.024mA	10.24mA	1.28mA	12.8mA	1.536mA	15.36mA	1.792mA	17.92mA	
Accuracy	±0.1% of (Reading + Range)										
Power Read Back											
Range (5 Digital)	10000W	15000W	10000W	20000W	10000W	25000W	10000W	30000W	10000W	35000W	
Resolution	0.1W	1W	0.1W	1W	0.1W	1W	0.1W	1W	0.1W	1W	
Accuracy	±0.125% of (Reading + Range)										
General											
Short Circuit											
Current	480A		640A		800A		960A		1120A		
Load ON Voltage											
0.4 ~ 100V											
Load OFF Voltage											
0 ~ 100V											
Power Consumption											
1450Wmax		1900Wmax		2350Wmax		2800Wmax		3250Wmax			
Operating Temperature²											
0~40°C											
Dimension (HxWxD)											
728x647x766mm			885x647x766mm			1041x647x766mm			1197x647x766mm		1353x647x766mm
HxWxD (Not included wheels)			781x647x766mm			937x647x766mm			1093x647x766mm		1249x647x766mm
Weight			170 kg		220 kg		280 kg		340 kg		390 kg
Safety & EMC											
CE											

冷卻方式：智慧型風扇冷卻

輸入電源：① Load-20KW內(含)：100~230 Vac ±10%，50/60Hz

② Load-25KW以上(含)：200~230 Vac ±10%，50/60Hz

註*1:CC Mode 可強制於range II

註*2:操作溫度範圍為0~40°C，此規格表內之精確度僅適用於25°C±5°C

訂 購 方 式

選購介面：

- ① GPIB Card
- ② RS232 Card
- ③ USB Card
- ④ LAN Card

選購配件：

吊環



規 格

MODEL	34240A		34305A		34310A		34315A		34320A	
Power	40KW		5KW		10KW		15KW		20KW	
Current	0 ~ 128A	0 ~ 1280A	0 ~ 5A	0 ~ 50A	0 ~ 10A	0 ~ 100A	0 ~ 15A	0 ~ 150A	0 ~ 20A	0 ~ 200A
Voltage	0 ~ 600V				0 ~ 1000V					
Min. Operating Voltage	10V @ 1280A		10V @ 50A		10V @ 100A		10V @ 150A		10V @ 200A	
Protections										
Over Power Protection (OPP)					105%				105%	
Over Current Protection (OCP)					104%				104%	
Over Voltage Protection (OVP)					105%				104%	
Over Temp Protection (OTP)					Yes				Yes	
Constant Current Mode										
Range*1	128A	1280A	5A	50A	10A	100A	15A	150A	20A	200A
Resolution	2.048mA	20.48mA	0.08mA	0.8mA	0.16mA	1.6mA	0.24mA	2.4mA	0.32mA	3.2mA
Accuracy	± (0.1% of Setting + 0.2% of Range)									
Constant Resistance Mode										
Range	5625Ω ~ 0.46875Ω	0.46875Ω~0.00787Ω	24000Ω~20Ω	20Ω~0.2004Ω	12000Ω~10Ω	10Ω~0.1002Ω	8332.5Ω~6.666Ω	6.6659Ω~0.066792Ω	6000Ω~5Ω	5Ω~0.0501Ω
Resolution	35.5μs	0.007875mΩ	0.833μS	0.334mΩ	1.666μS	0.167mΩ	2.4μS	0.11132mΩ	3.33μS	0.0835mΩ
Accuracy	±0.2% of (Setting + Range)									
Constant Voltage Mode										
Range			600V						10 ~ 1000V	
Resolution			10mV						16mV	
Accuracy	± 0.05% of (Setting + Range)									
Constant Power Mode										
Range	4000W	40000W	500W	5000W	1000W	10000W	1500W	15000W	2000W	20000W
Resolution	64mW	640mW	8mV	80mW	16mV	160mW	24mW	240mW	32mW	320mW
Accuracy	± 0.5% of (Setting + Range)									
Constant Voltage Mode + Constant Current Mode										
Range	600V	1280A	1000V	50A	1000V	100A	1000V	150A	1000V	200A
Resolution	10mV	20.48mA	16mV	0.8mA	16mV	1.6mA	16mV	2.4mA	16mV	3.2mA
Accuracy	± 1.0% of (Setting + Range)									
Constant Voltage Mode + Constant Power Mode										
Range	600V	40000W	1000V	5000W	1000V	10000W	1000V	15000W	1000V	20000W
Resolution	10mV	640mW	16mV	80mW	16mV	160mW	16mV	240mW	16mV	320mW
Accuracy	± 1.0% of (Setting + Range)									
MPPT Mode										
Algorithm	P&O + Scanning									
Load mode	CC, CR, CV (MPPT C, R, V)									
Sampling interval	10ms~2000ms ; resolution 1ms									
P&O interval	10ms~2000ms ; resolution 1ms									
Memory situation	Discard old data and keep catching new data									
Dynamic Mode										
Timing										
Thigh & Tlow	0.050~9.999 / 99.99 / 999.9 / 9999ms									
Resolution	0.001 / 0.01 / 0.1 / 1ms									
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm									
Slew Rate	0.1024A~6.4A/μs	1.024A~64A/μs	0.004A~0.25A/μs	0.04A~2.5A/μs	0.008A~0.5A/μs	0.08A~5A/μs	0.012A~0.75A/μs	0.12A~7.5A/μs	0.016A~1A/μs	0.16A~10A/μs
Resolution	25.6mA/μs	256mA/μs	0.001A/μs	0.01A/μs	0.002A/μs	0.02A/μs	0.003A/μs	0.03A/μs	0.004A/μs	0.04A/μs
Min. Rise Time	20μs(typical)									
Current										
Range	0~128A	128~1280A	0~5A	5~50A	0~10A	10~100A	0~15A	15~150A	0~20A	20~200A
Resolution	2.048mA	20.48mA	0.08mA	0.8mA	0.16mA	1.6mA	0.24mA	2.4mA	0.32mA	3.2mA
Measurement										
Voltage Read Back										
Range (5 Digital)	0~60V	60~600V	0~100V	100~1000V	0~100V	100~1000V	0~100V	100~1000V	0~100V	100~1000V
Resolution	1mV	10mV	1.6mV	16mV	1.6mV	16mV	1.6mV	16mV	1.6mV	16mV
Accuracy	±0.025% of (Reading + Range)									
Current Read Back										
Range (5 Digital)	0~128A	128~1280A	0~5A	5~50A	0~10A	10~100A	0~15A	15~150A	0~20A	20~200A
Resolution	2.048mA	20.48mA	0.08mA	0.8mA	0.16mA	1.6mA	0.24mA	2.4mA	0.32mA	3.2mA
Accuracy	±0.1% of (Reading + Range)									
Power Read Back										
Range (5 Digital)	10000W	40000W	1000W	5000W	1000W	10000W	10000W	15000W	10000W	20000W
Resolution	0.1W	1W	0.01W	0.1W	0.01W	1W	0.1W	1W	0.1W	1W
Accuracy	±0.125% of (Reading + Range)									
General										
Short Circuit										
Current	1280A		50A		100A		150A		200A	
Load ON Voltage	0.4 ~ 100V				10.4 ~ 200V					
Load OFF Voltage	0 ~ 100V				0 ~ 200V					
Power Consumption	3700Wmax		600 Wmax		1000Wmax		1450Wmax		1900Wmax	
Operating Temperature ²	0~40°C									
Dimension (HxWxD)	1509x647x766mm		573x647x766mm		573x647x766mm		728x647x766mm		885x647x766mm	
HxWxD (Not included wheels)	1405x647x766mm		469x647x766mm		469x647x766mm		625x647x766mm		781x647x766mm	
Weight	430 kg		100 kg		130 kg		170 kg		220 kg	
Safety & EMC	CE									

冷卻方式：智慧型風扇冷卻

輸入電源：① Load-20KW內(含)：100~230 Vac ±10%，50/60Hz

② Load-25KW以上(含)：200~230 Vac ±10%，50/60Hz

註*1:CC Mode 可強制於range II

註*2:操作溫度範圍為0~40°C，此規格表內之精確度僅適用於25°C±5°C


訂 購 方 式

選購介面：

- ① GPIB Card
- ② RS232 Card
- ③ USB Card
- ④ LAN Card

選購配件：

吊環



規 格

MODEL	34325A		34330A		34335A		34340A	
Power	25KW		30KW		35KW		40KW	
Current	0 ~ 25A	0 ~ 250A	0 ~ 30A	0 ~ 300A	0 ~ 35A	0 ~ 350A	0 ~ 40A	0 ~ 400A
Voltage	0 ~ 1000V							
Min. Operating Voltage	10V @ 250A		10V @ 300A		10V @ 350A		10V @ 400A	
Protections								
Over Power Protection (OPP)	105%							
Over Current Protection (OCP)	104%							
Over Voltage Protection (OVP)	104%							
Over Temp Protection (OTP)	Yes							
Constant Current Mode								
Range*1	25A	250A	30A	300A	35A	350A	40A	400A
Resolution	0.4mA	4mA	0.48mA	4.8mA	0.56mA	5.6mA	0.64mA	6.4mA
Accuracy	± (0.1% of Setting + 0.2% of Range)							
Constant Resistance Mode								
Range	4800Ω~4Ω	4Ω~0.04008Ω	3999.6Ω~3.333Ω	3.333Ω~0.0333396Ω	3428.4Ω~2.857Ω	2.857Ω~0.0286266Ω	3000Ω~2.5Ω	2.5Ω~0.02505Ω
Resolution	4.166μS	0.0668mΩ	5μS	0.05566mΩ	5.833μS	0.047711mΩ	6.66μS	0.04175mΩ
Accuracy	±0.2% of (Setting + Range)							
Constant Voltage Mode								
Range	10 ~ 1000V							
Resolution	16mV							
Accuracy	± 0.05% of (Setting + Range)							
Constant Power Mode								
Range	2500W	25000W	3000W	30000W	3500W	35000W	4000W	40000W
Resolution	40mV	400mW	48mV	480mW	56mW	560mW	64mW	640mW
Accuracy	± 0.5% of (Setting + Range)							
Constant Voltage Mode + Constant Current Mode								
Range	1000V	250A	1000V	300A	1000V	350A	1000V	400A
Resolution	16mV	4mA	16mV	4.8mA	16mV	5.6mA	16mV	6.4mA
Accuracy	± 1% of (Setting + Range)							
Constant Voltage Mode + Constant Power Mode								
Range	1000V	25000W	1000V	30000W	1000V	35000W	1000V	40000W
Resolution	16mV	400mW	16mV	480mW	16mV	560mW	16mV	640mW
Accuracy	± 1.0% of (Setting + Range)							
MPPT Mode								
Algorithm	P&O + Scanning							
Load mode	CC, CR, CV (MPPT C, R, V)							
Sampling interval	10ms~2000ms ; resolution 1ms							
P&O interval	10ms~2000ms ; resolution 1ms							
Memory situation	Discard old data and keep catching new data							
Dynamic Mode								
Timing								
Thigh & Tlow	0.050~9.999 / 99.99 / 999.9 / 9999ms							
Resolution	0.001 / 0.01 / 0.1 / 1ms							
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm							
Slew Rate	0.02A~1.25A/μs	0.2A~12.5A/μs	0.024A~1.5A/μs	0.24A~15A/μs	0.028A~1.75A/μs	0.28A~17.5A/μs	0.032A~2A/μs	0.32A~20A/μs
Resolution	0.005A/μs	0.05A/μs	0.006A/μs	0.06A/μs	0.007A/μs	0.07A/μs	0.008A/μs	0.08A/μs
Min. Rise Time	20μs(typical)							
Current								
Range	0~25A	25~250A	0~30A	30~300A	0~35A	35~350A	0~40A	40~400A
Resolution	0.4mA	4mA	0.48mA	4.8mA	0.56mA	5.6mA	0.64mA	6.4mA
Measurement								
Voltage Read Back								
Range (5 Digital)	0~100V	100~1000V	0~100V	100~1000V	0~100V	100~1000V	0~100V	100~1000V
Resolution	1.6mV	16mV	1.6mV	16mV	1.6mV	16mV	1.6mV	16mV
Accuracy	±0.025% of (Reading + Range)							
Current Read Back								
Range (5 Digital)	0~25A	25~250A	0~30A	30~300A	0~35A	35~350A	0~40A	40~400A
Resolution	0.4mA	4mA	0.48mA	4.8mA	0.56mA	5.6mA	0.64mA	6.4mA
Accuracy	±0.1% of (Reading + Range)							
Power Read Back								
Range (5 Digital)	10000W	25000W	10000W	30000W	10000W	35000W	10000W	40000W
Resolution	0.1W	1W	0.1W	1W	0.1W	1W	0.1W	1W
Accuracy	±0.125% of (Reading + Range)							
General								
Short Circuit								
Current	250A		300A		350A		400A	
Load ON Voltage								
	10.4 ~ 200V							
Load OFF Voltage								
	0 ~ 200V							
Power Consumption								
	2350 Wmax		2800Wmax		3250Wmax		3700Wmax	
Operating Temperature²								
	0~40°C							
Dimension (HxWxD)								
	1041x647x766mm		1197x647x766mm		1353x647x766mm		1509x647x766mm	
HxWxD (Not included wheels)								
	937x647x766mm		1093x647x766mm		1249x647x766mm		1405x647x766mm	
Weight								
	280 kg		340 kg		390 kg		430 kg	
Safety & EMC								
	CE							

冷卻方式：智慧型風扇冷卻

輸入電源：① Load-20KW內(含)：100~230 Vac ±10%，50/60Hz

② Load-25KW以上(含)：200~230 Vac ±10%，50/60Hz

註*1:CC Mode 可強制於range II

註*2:操作溫度範圍為0~40°C，此規格表內之精確度僅適用於25°C±5°C


訂 購 方 式

選購介面：

- ① GPIB Card
- ② RS232 Card
- ③ USB Card
- ④ LAN Card

選購配件：

吊環



34325A 1000V · 250A · 25KW



34330A 1000V · 300A · 30KW



34335A 1000V · 350A · 35KW



34340A 1000V · 400A · 40KW