

IP65 Detachable probe pH pen 8687/8688/8689

- Big LCD for pH/ temperature real time display
- Electrode status indication
- Easy electrode replacement
- Stability indicator
- One touch auto-calibration up to 3 points
- Calibration values are adjustable
- Cap to keep sensor wet & last life time



8689



Auto Power Off



Auto Temp. Compensation



Metric/Imperial



Low Battery



HOLD



IP65




8687



8688

Model	8687	8688	8689
pH range	2.0~12.0	0.0~14.0	0.00~14.00
pH accuracy	+/-0.3	+/-0.2	+/-0.05
pH resolution	0.1	0.1	0.01
Temp. range	0~50.0°C	0~50.0°C	0~50.0°C
Temp. accuracy	+/-1°C	+/-1°C	+/-0.5°C
Temp. resolution	0.1	0.1	0.1
ATC	ATC	ATC	ATC
LCD size	30(H)x18(W)mm		
Operating temp.	0~60°C		
Operating RH%	Humidity<80%		
Storage temp.	0~60°C		
Storage RH%	Humidity < 90%		
Sensor life time	>6 months (with good maintenance)		
Dimension	176(L)x39(W)x39(H)mm		
Weight	110g		
Battery	LR44 x 4pcs		
Optional	Detachable pH electrode		
Standard Package	Meter/Battery/Manual/Wrist strap/Paper box		

3 steps to replace probe:



Optional:



PH ELECTRODE
FOR 8687/8688/8689
P/N: VZ86P8AZ

Ordering Code

VZ8687AZ, 8687 pH pen

VZ8688AZ, 8688 pH pen

VZ8689AZ, 8689 pH pen

VZ86P8AZ, pH replacement probe