




**5V UNIVERSAL ADAPTOR**  
 P/N:VZ12405A  
 Input:100~240 VDC  
 Output:5VDC, 0.6A  
 4 plugs included:US/UK/EU/AU



**Ordering Code**  
**VZ87797AZ, 87798 logger**  
**VZ87799AZ, 87799 logger**  
**VZ12405A, 5V universal adaptor**

## Desktop Temp./Humidity Monitor with SD Card Logging 87798/87799

- Simultaneously display/record Temp. and Humidity
- Advanced SD card design for continuous recording
- Check vapor condensation risk through DP temperature
- Long battery life (via alkaline battery)
  - no logging: one year    -logging: one month (rate:1min, 1G SD card)
- LED/Audible alarm threshold of each parameters are programmable
- 87798:Dew point monitor    87799:External T monitor



Model	87798	87799
Temp. range	-10.0~70.0°C	
Temp. resolution	0.1°C/°F	
Temp. accuracy	+/-1°C	
Humidity. range	0%~99.9%RH	
Humidity resolution	0.1%RH	
Humidity accuracy	+/-3%RH (at 25°C, 10~90%RH, others +/-5%RH)	
Dew point temp. Range	-20~70°C	N/A
External temp. Range	N/A	-10~70°C (Display: -30~70°C)
External temp. resolution	N/A	0.1°C/°F
External temp. accuracy	N/A	+/-0.6°C (0~50°C), +/-1.2°C(-10~0°C, 50~70°C) No specified for -30°C~-10°C
External probe size	N/A	Dia.4mm x Length:25mm
External probe cable	N/A	2M long, material: PVC
SD card	SD card or SDHC card (MMC and SDXC cards are not compatible)	
Sampling rate	1 to 720 mins. Default:10 mins	
Beeper (dB)	~65dB	
RH% Self calibration	YES, via salt chamber	
Power consumption	<0.4mA	
LCD size (mm)	63(H)x70(W)	
Operation temp.	0~50°C	
Operation RH%	Humidity < 90%	
Storage temp.	-10~50°C	
Storage RH%	Humidity < 90%	
Dimension(mm)	110x91x30(H)	
Weight	~200g	
Power	AA x3pcs or 5V adaptor	
Standard Package	Meter/adaptor/Manual/Paper box/SD card	

### What is Dew Point (DP)?

The DP is the temperature at which the air can't hold all of its water vapor and some of the water vapor must condense into liquid water. Condensation of water vapour begins when the temp. of air is lowered to its dew point and beyond.

### What is the application of Dew Point?

- In summer or high humidity season, identifies and warns when conditions for mold growth exist
- In winter or low humidity season, identifies and warns when conditions for static electricity exist
- Air temperature and dew point temp. indicate where condensation may occur
- Monitor conditions in laboratories, basement and other controlled environment settings

