

GOTECH "the best partner" to raise your competition

GT-7012-AB AKRON耐磨試驗機 Akron Abrasion Tester

本機適用於硫化橡膠及彈性材料耐磨性能測試。通過量測試樣與砂輪摩擦後之磨耗體積，判定其耐磨性能。可設定磨耗轉數，到達設定轉數並自動停機。

This tester is designed to use together with a special balance for testing the abrasive consumption for the rubber products such as tire, belt of tank, ...etc.

磨耗砂輪 Grinding Wheel	外徑150mm · 厚度25mm · 粒度40# Outside dia Φ 150mm · 25mm(w) · grit 40#
砂輪軸回轉速 Grinding wheel rotating speed	35 \pm 1 r.p.m.
膠輪軸回轉速 Specimen Rotating speed	85 \pm 1 r.p.m.
試驗荷重 Load	1 kg 砝碼 為使用預磨輪預磨砂輪用 6 LB 砝碼 配4.54 kg荷重 2 LB 砝碼 配2.75 kg荷重(另購)
試樣傾斜角度範圍 Specimen Slanted Range	0° ~ 35° 可調 adjustable
計數器 Counter	LCD 液晶顯示 0 ~ 99,999,999次 可設定
體積 Dimension (W×D×H)	57×52×45 cm
重量(約) Weight (approx.)	60 kg
電源 Power	1 ϕ AC 220V (依國別或指定 or specify)



瞭解更多產品信息，請登錄我司網站 www.gotech.biz