



高鐵儀器 精密卓越



GOTECH "the best partner" to raise your competition

GT-7005-C2N 電腦式恆溫恆濕試驗機 Micro-Computer Temperature & Humidity Tester

本機提供可控制、調整溫度、濕度之環境,以試驗各種材料耐熱、耐寒、耐乾、耐濕、性能適合塑膠製品、電子、電器、食品、車輛、金屬、化學、建材等工廠品管和產品研發之用,可於短時間內分辨產品性能,為改進配方提高品質提供可靠依據。

The temperature and humidity tester, also known as environmental chamber, is commonly used in nearly every industry for simulating the effect of climate to manufactured products or materials.



溫度範圍 Temp. range	-20°C ~ +100°C
濕度範圍 Humidity range	15 ~ 98%RH
溫度波動度 Temp. fluctuation	±0.3°C
溫度均勻度 Temp. uniformity	±1.0°C
溫度偏差 Temp. accuracy	±1.0°C
溫度精度 Temp. display resolution	0.01°C
濕度精度 Humidity display resolution	0.1%RH
濕度偏差 Humidity accuracy	±2.0%RH
濕度均勻度 Humidity uniformity	3.0%RH
升溫時間 Heating up time	20 ~ 100°C 約35分鐘 within 35min
降溫時間 Cooling down time (空箱體及環境溫度26°C以下時) (ambient temp. below 26°C w/o load)	20 ~ -20°C 約50分鐘 within 50min
通訊 Communication Interface	RJ45網線100米內 (另購 optional)
內箱尺寸 (W × D × H)cm Interior dimensions	50×60×75 cm (W×D×H)
體積 Exterior dimension (W×D×H)	85×150×180 cm (W×D×H)
重量 Weight	379 kg
電源 Power	3φ AC 380V 50Hz/60Hz(依國別或指定 or specify)

瞭解更多產品資訊，請登錄我司網站 www.gotech.biz



創於1977年
高鐵路科技股份有限公司
GOTECH TESTING MACHINES INC.
本廠: 台中市工業區24路28號
二廠: 台中市工業區24路31號
TEL: (04)23590061 FAX: (04)23591553
網址: www.gotech.biz E-mail: gt112@gotech.biz

高鐵路檢測儀器(東莞)有限公司
GOTECH TESTING MACHINES CO., LTD.
地址: 中國廣東省東莞市南城街道宏三路2號
TEL: 0769-89986666 22400899 FAX: 0769-22400699
E-mail: gt-d130@gotech.biz 手機: 13926831580

高特威爾檢測儀器(青島)有限公司
GOODTECHWILL TESTING MACHINES CO., LTD.
地址: 中國山東省青島市城陽區招商網穀合心園19號樓101
TEL: 0532-85931956 85931957 FAX: 0532-85931950
E-mail: gt-q101@gotech.biz 手機: 13708970121