



高鐵儀器 精密卓越





 ISO 9001

GOTECH "the best partner" to raise your competition

GT-6022-D 層間剝離強度試驗機(數位式) Internal Bond Tester

TAPPI-UM403

試樣受一定角度、一定重量衝擊後，所能吸收之能量，並指示瓦楞紙板層間剝離強度。設計符合TAPPI-UM403標準需求。

The energy absorbed is measured after the specimen is impacted at a given angle and weight, and the interlaminar peeling strength of a corrugated board is indicated. It is designed in accordance with TAPPI-UM403.

衝擊角度 Impact angle	90°
容量 Capacity	0 ~ 0.25 ft-lb 0 ~ 0.50 ft-lb
控制方式 Control device	HMI(觸摸屏 Touch screen)+PLC
臂軸心至衝擊端中心線距離 Length from axis of pendulum arm to center line of impact end	228.1mm
衝擊頭直徑 Dart diameter	8.0 mm
試樣數量 Number of specimens	5 組sets
體積(約) Dimensions (approx.)	60x51x63 cm (W*D*H)
重量(約) Weight (approx.)	42 kg



瞭解更多產品資訊，請登錄我司網站 www.gotech.biz



創於1977年——
高鐵科技股份有限公司
GOTECH TESTING MACHINES INC.

本廠: 台中市工業區24路28號
二廠: 台中市工業區24路31號
TEL: (04)23590061 FAX: (04)23591553
網址: www.gotech.biz E-mail: gt112@gotech.biz

高鐵檢測儀器有限公司

GOTECH TESTING MACHINES CO., LTD.

地址: 廣東省東莞市南城區宏圖高科技開發區宏三路
TEL: 0769-89986666 22400899 FAX: 0769-22400699
E-mail: gt-d130@gotech.biz 手機: 13926831580

高特威爾檢測儀器有限公司

GOODTECHWILL TESTING MACHINES CO., LTD.

地址: 中國青島市市北區哈爾濱路52號青建太陽島1號商務樓8層
TEL: 0532-85931956 85931957 FAX: 0532-85931950
E-mail: gt-q101@gotech.biz 手機: 13708970121