

MBX1

Technical Data



MBX1 Technical Data

© OMICRON electronics GmbH 2022. All rights reserved.

This technical data sheet was extracted from the following document: ENU 1218 03 07

All rights including translation reserved. Reproduction of any kind, for example, photocopying, microfilming, optical character recognition and/or storage in electronic data processing systems, requires the explicit consent of OMICRON. Reprinting, wholly or in part, is not permitted.

The document content represents the technical status at the time of writing and are subject to change without prior notice.


We have done our best to ensure that the information given in this manual is useful, accurate and entirely reliable. However, OMICRON does not assume responsibility for any inaccuracies which may be present. The user is responsible for every application that makes use of an OMICRON product.

OMICRON translates this document from the source language English into a number of other languages. Any translation of this manual is done for local requirements, and in the event of a dispute between the English and a non-English version, the English version of this manual shall govern.


Contents

1	Device overview	4
2	MBX1 technical data	6
2.1	Computing performance	6
2.2	Mechanical data	6
2.3	External power supply unit	6
2.4	Connectors	7
2.5	Environmental conditions	8
2.6	Electromagnetic compatibility and safety standards	8

1 Device overview



Front view		
1	STATION – A, B, C, D	Ethernet connectors for connection to substation and accessory devices
2	Power button	Button to switch the <i>MBX1</i> on and off The LED lights up when the <i>MBX1</i> is switched on.



Back view		
1	CTRL1, CTRL2	Ethernet connectors for connection to computer
2	Grounding screw	For connection to ground (e.g. with a 6 m/19.8 ft grounding cable with a battery clamp and an M6 cable lug)
3	DC INPUT	Connection to power supply
–	Display port	<i>Future use</i>
–	HDMI port	<i>Future use (service port)</i>
–	USB ports	<i>Future use</i>

2 MBX1 technical data

2.1 Computing performance

Computing performance	
Processors	Secure cryptoprocessor according to TPM 2.0 (ISO/IEC 11889) Dual-core processor with hardware multithreading
Memory	8 GB memory 64 GB SSD

2.2 Mechanical data

Mechanical data	
Weight	2.4 kg 5.3 lb
Dimensions W × H × D	180 × 80 × 180 mm 7.1 × 3.15 × 7.1 in
Ingress protection	IP30

2.3 External power supply unit

AC power supply	
Connection	C14 connector in accordance with IEC 60320-1
Power connector	Standard DC barrel jack, positive center pin Ø 2.1 × 5.5 × 11 mm Ø 0.08 × 0.22 × 0.43 in
Input voltage, single phase	
Nominal voltage	100 V _{AC} ... 240 V _{AC}
Maximum input current	1.8 A
Overvoltage category	II
Output	
Output voltage	12 V _{DC} (±5 %)
Output power	96 W
Frequency	
Nominal frequency	50 Hz / 60 Hz
Operational range	47 Hz ... 63 Hz (±1 Hz)

2.4 Connectors

Ethernet ports CTRL1 and CTRL2	
Type	10/100/1000Base-TX
Connector	RJ45
Cable type	LAN cable of category 5 (CAT5) or better
Status indication	Green LED: physical link present
	Yellow LED: traffic on interface

Ethernet ports STATION A, B, C, D	
Type	10/100/1000Base-TX
Connector	RJ45
Cable type	LAN cable of category 5 (CAT5) or better
Status indication	Green LED: physical link present
	Yellow LED: traffic on interface

USB	
Type	USB 3.0 (<i>SuperSpeed</i> , 5 GBit/s)
Connector	USB type A

HDMI (service port)	
Type	HDMI 1.4, 3840 × 2160 at 30 Hz
Connector	HDMI type A

Display port	
Type	DisplayPort 1.2, 3840 × 2160 at 60 Hz
Connector	Full-size DisplayPort

2.5 Environmental conditions

Environmental conditions		
Temperature	Operating	0 °C ... +45 °C 32 °F ... 113 °F
	Storage	-20 °C ... +80 °C -4 °F ... +176 °F
Maximum altitude	Operating	4,000 m 13,123 ft
	Storage	15,000 m 49,212 ft
Humidity	20 % ... 80 % relative humidity; non-condensing	

2.6 Electromagnetic compatibility and safety standards

Electromagnetic compatibility (EMC)

Electromagnetic interference (EMI)	
Europe	EN 61326-1
	EN 61000-3-2/3, EN 55032 (Class B)
International	IEC 61326-1
	IEC 61000-3-2/3
	CISPR 32 (Class B)
USA	47 CFR 15 Subpart B (Class B) of FCC

Electromagnetic susceptibility (EMS)	
Europe	EN 61326-1 (industrial electromagnetic environment)
	EN 61000-6-5 (substation/interface type 2) ¹
International	IEC 61326-1 (industrial electromagnetic environment)
	IEC 61000-6-5 (substation/interface type 2) ¹

¹ Classified as passive monitoring equipment.

Safety standards	
Europe	EN 62368-1
International	IEC 62368-1
USA	UL 62368-1
Canada	CAN/CSA-C22.2 No 62368-1
Certificates	