

AC119 Series

Biaxial Accelerometer, Side Exit 3 Pin Connector, 100 mV/g, with X and Z Axis, $\pm 15\%$



VIBRATION ANALYSIS HARDWARE



Product Features


Low Cost Biaxial Sensor

- ▶ 100 mV/g/axis ($\pm 15\%$)
- ▶ Monitor 2 Channels of Data Simultaneously
- ▶ Compatible with C509 and A3AB connectors

AC119-1D

3 Pin Connector

Connector Pin	Polarity
A (Axis X)	(+) Signal/Power
B (Axis Z)	(+) Signal/Power
C	(-) Common/Grid




Stock Product

AC119-2D

CB105 Integral Cable

Conductor	Polarity
Green (Axis X)	(+) Signal/Power
White (Axis Z)	(+) Signal/Power
Black	(-) Common/Grid




Built To Order

AC119-3D

CB218 Armored Integral Cable

Conductor	Polarity
Green (Axis X)	(+) Signal/Power
White (Axis Z)	(+) Signal/Power
Black	(-) Common/Grid



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC119	M/AC119	Environmental		
Sensitivity ($\pm 15\%$)		100 mV/g	Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response ($\pm 3\text{dB}$)	60-390,000 CPM	1,0-6500 Hz	Electromagnetic Sensitivity		CE
Dynamic Range		± 50 g, peak	Sealing		Welded, Hermetic
Electrical			Submersible Depth	200 ft.	60 m
Settling Time		<2.5 seconds	Physical		
Voltage Source (IEPE)		18-30 VDC	Sensing Element		PZT Ceramic
Constant Current Excitation		2-10 mA	Sensing Structure		Shear Mode
Spectral Noise @ 10 Hz		27 $\mu\text{g}/\sqrt{\text{Hz}}$	Weight	6.9 oz	195 grams
Spectral Noise @ 100 Hz		6.5 $\mu\text{g}/\sqrt{\text{Hz}}$	Case Material		316L Stainless Steel
Spectral Noise @ 1000 Hz		2.5 $\mu\text{g}/\sqrt{\text{Hz}}$	Mounting		1/4-28
Output Impedance		<100 ohm	Connector (Non-Integral)		C509, C519
Bias Output Voltage		10-14 VDC	Mounting Torque	1 to 2 ft. lbs.	1,4 to 2,7 Nm
Case Isolation		>10 ⁹ ohm	Mounting Hardware	1/4-28 Captive Bolt	M6x1 Captive Bolt
			Calibration Certificate		CA10

Typical Frequency Response

