

# 直流取向电源

## DC Aligning Magnetizer

典型机型/Typical Model:

KD200-60A, KD400-350AB, KD400-350AC, KDT300-120A, KDT400-300A

功能:

- 采用 PLC 电脑控制，触摸屏显示功能；
- 充磁电流数字、指针表双重显示；10A~60A 间任意可调；
- 有欠电流保护，防止充磁不饱和现象；
- 产量计数功能；

Features:

- Controlled by PLC and has a touch screen;
- Current displayed by both digital screen and point; current range is 10A ~ 60A;
- Has undercurrent protection to avoid magnetization unsaturated;
- Has counting function;



型号 Model	KD200-60A	KD400-350AB/AC	KDT300-120A	KDT400-300A
输入电压 Input Voltage	AC 380V ± 20V	AC 380V ± 20V	AC 380V ± 20V	AC 380V ± 20V
最大输出电压 Max. Output Voltage	DC 200V	DC 400V	DC 300V	DC 400V
最大输出电流 Max. Output Current	60 (A)	350 (A)	120 (A)	300 (A)
输出负载 Output Load	水冷取向线圈 /water-cooled aligning coil	TY250-60S	水冷取向线圈 /water-cooled aligning coil	水冷取向线圈 /water-cooled aligning coil
外形尺寸 Dimensions	W D H 550×470×1240	W D H 700×1620×1550	W D H 550×450×1260	W D H 550×470×1240
重量 Weight	100 KG	1200KG	100 KG	200 KG