

脉冲取向电源

Pulsed Aligning Magnetizer

典型机型 / Typical Model

MCJ-2010-3G, MCJ-2010-3GT, MCJ-3010-3G, MCJ-3010-3GT, MCJ-3020-3G,

MCJ-3020-3GT



功能:

- 一次操作，充磁机自动进行数次正向放电(一次反向放电若带有反充功能)。
- 放电电压独立可调，独立显示。
- 机器工作状态可通过触摸显示控制器监看。
- 采用 PLC 电脑控制。
- 充/退磁电流数字、指针表双重显示
- 每次脉冲间隔可调。

Features:

- The magnetizer can discharge multiple times per operation (and reverse discharge for some models)
- The voltage can be adjusted and displayed.
- The operation mode can be monitored by the touch screen.
- Controlled by PLC.
- The current is displayed by both digital screen and a pointer.
- The gap between the pulses can be adjusted.

型号 Model	MCJ-2010-3G	MCJ-2010-3GT	MCJ-3010-3G	MCJ-3010-3GT	MCJ-3020-3G	MCJ-3020-3GT
输入电压	AC 220V	AC 220V	AC 220V	AC 220V	AC 220V	AC 220V
输出电压	2000V	2000V	3000V	3000V	3000V	3000V
最大输出电流	40000A	40000A	40000A	40000A	40000A	40000A
电容分配	充磁 1 1000uF	充磁 1 1000uF	充磁 1 1000uF	充磁 1 1000uF	充磁 1 2000uF	充磁 1 2000uF
	充磁 2 1000uF	充磁 2 1000uF	充磁 2 1000uF	充磁 2 1000uF	充磁 2 2000uF	充磁 2 2000uF
	充磁 3 1000uF	反充 1000uF	充磁 3 1000uF	反充 1000uF	充磁 3 2000uF	反充 2000uF