


ASM 306 S



ASM 306 S, Profibus

- Highest reliability and accuracy for full-time testing operation
- Fast, repeatable and high sensitivity measurements
- Compact unit with intuitive menu for easy operation
- Probe and test leak to be ordered separately

Dimensions



Technical Data	ASM 306 S, Profibus
Test method	Sniffing leak detection
I/O interfaces	Profibus
Interface: Connection, device side	Standard 15 pins I/O
Operating temperature	10 – 40 °C
Input voltage(s)	100 – 240 V AC, 50/60 Hz
Emission sound pressure level (EN ISO 2151)	55 dB(A)
Start-up time (20°C) without calibration	2 min
Minimum detectable leakage rate for helium (sniffing leak detection)	$1 \cdot 10^{-8}$ Pa m ³ /s $1.33 \cdot 10^{-6}$ Torr l/s $1 \cdot 10^{-6}$ mbar l/s
Weight	22 kg 48.5 lb
Detectable gases	⁴ He ³ He H ₂
Response time	1 s
Dimensions (L x W x H)	350 x 305 x 421 mm
Power consumption max.	300 VA
Backing pump	With oil-free backing pump

Order number	ASM 306 S, Profibus
ASM 306 S, Profibus	RSAS00A8MM9A

Your Success. Our Passion.

We give our best for you every day –
worldwide!

Are you looking for an optimum vacuum solution?

Talk to us:
Pfeiffer Vacuum GmbH
Germany
T +49 6441 802-0

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 9/7/2024

Follow Us On Social Media
#pfeiffervacuum



www.pfeiffer-vacuum.com

PFEIFFER  **VACUUM**